

Revision date:
25.11.2021

Bizol Coolant Asia

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bizol Coolant Asia

Further trade names

UFI: 7R10-40QD-K00W-2SR7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Antifreeze agent

1.3. Details of the supplier of the safety data sheet

Company name:	BIZOL Germany GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 (30) 804 869-0	Telefax: +49 (30) 804 869-2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

1.4. Emergency telephone number:

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 -
08454 24 24 24 In Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Acute Tox. 4; H302
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements


GB CLP Regulation

Hazard components for labelling

ethanediol
2,2' -oxybisethanol

Signal word: Warning

Pictograms:



Hazard statements

H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe vapour.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P314 Get medical advice/attention if you feel unwell.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No further relevant information available.

SECTION 3: Composition/information on ingredients

Revision date:
25.11.2021

Bizol Coolant Asia

Page 2 of 9

3.2. Mixtures

Chemical characterization

Glycol-based mixture.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
107-21-1	ethanediol			70 - 90 %
	203-473-3	603-027-00-1	01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373			
111-46-6	2,2' -oxybisethanol			< 1,5 %
	203-872-2	603-140-00-6	01-2119457857-21	
	Acute Tox. 4, STOT RE 2; H302 H373			
1310-58-3	potassium hydroxide			< 0,45 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318			
7664-38-2	phosphoric acid			< 0,45 %
	231-633-2	015-011-00-6	01-2119485924-24	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H290 H302 H314 H318			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
107-21-1	203-473-3	ethanediol	70 - 90 %
		dermal: LD50 = 3500 mg/kg; oral: LD50 = 1600 mg/kg	
111-46-6	203-872-2	2,2' -oxybisethanol	< 1,5 %
		dermal: LD50 = 11890 mg/kg; oral: ATE = 500 mg/kg	
1310-58-3	215-181-3	potassium hydroxide	< 0,45 %
		oral: LD50 = 365 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	
7664-38-2	231-633-2	phosphoric acid	< 0,45 %
		dermal: LD50 = 2740 mg/kg; oral: LD50 = 1250 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

Revision date:
25.11.2021

Bizol Coolant Asia

Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO₂). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Protective measures: see section 7 + 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Protective measures: see section 7 + 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

No special measures are necessary.

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Revision date:
25.11.2021

Bizol Coolant Asia

Page 4 of 9

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-46-6	2,2'-Oxydiethanol	23	101		TWA (8 h)	WEL
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
7664-38-2	Orthophosphoric acid	-	1		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
107-21-1	ethanediol			
	Worker DNEL, long-term	inhalation	local	35 mg/m ³
	Consumer DNEL, long-term	inhalation	local	7 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	53 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	106 mg/kg bw/day
111-46-6	2,2' -oxybisethanol			
	Worker DNEL, long-term	dermal	systemic	106 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	53 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	60 mg/m ³
	Consumer DNEL, long-term	inhalation	local	12 mg/m ³
1310-58-3	potassium hydroxide			
	Worker DNEL, long-term	inhalation	local	1 mg/m ³
	Consumer DNEL, long-term	inhalation	local	1 mg/m ³
7664-38-2	phosphoric acid			
	Worker DNEL, long-term	inhalation	local	1 mg/m ³
	Worker DNEL, long-term	dermal	systemic	10,7 mg/kg bw/day
	Worker DNEL, acute	inhalation	local	2 mg/m ³
	Consumer DNEL, long-term	oral	systemic	0,1 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	4,57 mg/m ³

PNEC values

CAS No	Substance	Value
	Environmental compartment	
107-21-1	ethanediol	
	Freshwater	10 mg/l
	Marine water	1 mg/l
	Freshwater sediment	20,9 mg/kg
	Micro-organisms in sewage treatment plants (STP)	199,5 mg/l
	Soil	1,53 mg/kg
111-46-6	2,2' -oxybisethanol	
	Freshwater	10 mg/l
	Marine water	1 mg/l
	Freshwater sediment	20,9 mg/kg
	Soil	1,53 mg/kg

8.2. Exposure controls

Revision date:
25.11.2021

Bizol Coolant Asia

Page 5 of 9

Appropriate engineering controls

See section 7. No additional measures necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection.

Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (EN 149), e.g. FFA P / FFP3.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	green
Odour:	characteristic

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	150 - 173 °C
Pour point:	not determined
Flash point:	111 °C
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Auto-ignition temperature:	not determined
Decomposition temperature:	No information available.
pH-Value:	7,0 - 9,0
Viscosity / dynamic:	not determined
Viscosity / kinematic: (at 25 °C)	18 mm ² /s
Flow time:	not determined
Water solubility:	completely miscible
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,13 g/cm ³
Relative vapour density:	not determined

9.2. Other information

Other safety characteristics

Evaporation rate:	not determined
-------------------	----------------

Further Information

No information available.

Revision date:
25.11.2021

Bizol Coolant Asia

Page 6 of 9

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1693,5 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-21-1	ethanediol				
	oral	LD50 mg/kg 1600		Practical experience/human evidence	
	dermal	LD50 mg/kg 3500	Mouse		
111-46-6	2,2' -oxybisethanol				
	oral	ATE mg/kg 500			
	dermal	LD50 mg/kg 11890	Rabbit		
1310-58-3	potassium hydroxide				
	oral	LD50 mg/kg 365	Rat		
7664-38-2	phosphoric acid				
	oral	LD50 mg/kg 1250	Rat		
	dermal	LD50 mg/kg 2740	Rabbit		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (ethanediol)

Revision date:
25.11.2021

Bizol Coolant Asia

Page 7 of 9

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
107-21-1	ethanediol					
	Acute fish toxicity	LC50 72860 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 6500-13000 mg/l	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna (Big water flea)		
	Fish toxicity	NOEC 15380 mg/l	7 d	Pimephales promelas (fathead minnow)		
	Crustacea toxicity	NOEC 8590 mg/l	7 d	Ceriodaphnia Dubia		

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
107-21-1	ethanediol			
	Biodegradation	90-100	10	
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-21-1	ethanediol	-1,36
111-46-6	2,2' -oxybisethanol	-1,98 (25°C)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions,

Revision date:
25.11.2021

Bizol Coolant Asia

Page 8 of 9

covering waste and dangerous waste.

List of Wastes Code - residues/unused products

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine pollutant: NO

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Revision date:
25.11.2021

Bizol Coolant Asia

Page 9 of 9

Changes

This data sheet contains changes from the previous version in section(s): 1,2,7,9,11,15.

Abbreviations and acronyms

- ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
- RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organization
- CAS: Chemical Abstracts Service (a division of the American Chemical Society)
- DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level
- PNEC: Predicted No Effect Concentration
- WEL (UK): Workplace Exposure Limits
- TWA (EC): Time-Weighted Average
- STEL (EC): Short Term Exposure Limit
- ATE: Acute Toxicity Estimate
- LD50: Lethal Dose, 50% (median lethal dose)
- LC50: Lethal Concentration, 50% (median lethal concentration)
- EC50: half maximal Effective Concentration
- ErC50: EC50 in terms of reduction of growth rate
- AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H373 May cause damage to kidneys through prolonged or repeated exposure if swallowed.
- H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). -----

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)